

CC4 CALL POINT

The CC4 Call Point is a sophisticated, intelligent call unit and the basic building block of CC4 systems. It can be configured to make any required call type, has Call and Cancel buttons, with provision for an optional, pluggable handset. It also contains the Infra-red and RF communication systems to support the CareCall4 Real-time Location System.

The Call button is touch sensitive, and a simulated touch test at pre-determined intervals provides ongoing certainty that the call point will operate correctly when needed. A secondary switch provides tactile feedback, along with the reassurance LED, and a momentary beep when a call is made.



Features:

- Configurable to be used as any of the call types specified in the Australian Standard AS3811.
- Automatic Nurse Presence feature. When a staff member wearing a CC4 badge enters a room, Nurse Presence state is automatically triggered. The over-door light illuminates green, and resident Call buttons are upgraded to Staff Assist.
- Real-time Location. The call points form a network using both Infra-red and radio frequency communication to reliably locate Staff Badges, and Resident Tags.
- A resident Call button can be used to make a higher priority call e.g., Staff Assist or Emergency by pressing the Call button three or more times in rapid succession.
- The call point can be programmed with a failover display message that becomes active if the server is offline.
- Call point functions highly configurable, providing flexibility for a wide range of applications.
- Software based configuration, allowing for remote reconfiguration by technicians.
- Provision for connecting accessory device inputs or outputs.
- Backlit Call and Reset buttons for easy use in low-light conditions.
- Flush wall mountable Call Point using a Standard Clipsal Series 2000 plate and mounting box for easy installation.
- Durable antibacterial sealed buttons for easy clean and low maintenance.
- All call types available in either horizontal or vertical orientation.



TECHNICAL SPECIFICATIONS

Dimensions (H x W x D)	113 x 73 x 22 mm.
Weight	85g without socket, 95g with socket.
Mounting method	Screw x2.
Termination	RJ-45 Network connections. Screw Terminals for accessory wiring.
Housing	Clipsal 2000 series plate.
Cable	Cat 6 cable for CareCall network.

ORDERING INFORMATION

C4-CPCL-M-PC-EM/PC	Patient Call with handset jack
C4C4-CPCL-M-PC-XX	Patient Call
C4-CPCL-M-EM-EM/PC	Emergency Call with handset jack
C4-CPCL-M-EM-XX	Emergency Call
C4-CPCL-M-SA-XX	Staff Assist Call
C4-CPCL-M-CB-XX	Code Blue Call
C4-CPCL-M-HA-XX	Home Away
C4-CPCL-M-DU-XX	Duress Call

Available in **Horizontal** configuration, replace CPCL with **CPHCL**.

