

OVER DOOR / CORRIDOR LIGHT

The LED light is a multi-colour over door LED priority indicator designed to give a visual indication of calls and priority levels. These are typically installed in corridors and above doors to indicate location of active call. LED lamps have three modes; steady, flash, and fast flash to further differentiate priority.



Technical Data

Part Number	LDL
Ambient temperature	5 °C to 55°C
Type of protection	IP 33 (when mounted with cover installed)
Material	PC + ABS
Colour	White
Fixing / mounting	Surface mount on wall or ceiling
Dimensions	L 115mm W 72mm D 62mm
Weight	Approx. 100g
LED light standard colours	Red, Orange and Green
LED colour options	Fully customisable

Pin No.	Name	Description
1	LED 1 Red	Anode +24v
2	LED 1 Red	Cathode
3	LED 2 Green	Anode +24v
4	LED 2 Orange	Cathode
5	LED 3 Green	Anode +24v
6	LED 3 Green	Cathode
7	NC	NC
8	NC	NC

Colour	Mode
Green	Steady, Flash, Fast Flash
Amber	Steady, Flash, Fast Flash
Red	Steady, Flash, Fast Flash
Blue*	Steady, Flash, Fast Flash

*note blue is an option

- can displace any other colour

The CarePlus™ Over Door Light is UL1069 and DIN 0834 certified, and meets AS3811.



AUTHORISED DISTRIBUTOR

USA office:

Europe / UK office:

Australian office: